

# DANDY SACK® FRAMED MODEL INLET PROTECTION SYSTEM GUIDE SPECIFICATION

PRODUCT:

DANDY SACK® FRAMED MODEL

MANUFACTURER:

Dandy Products Inc.  
P.O. Box 1680  
Powell, Ohio 43065  
Phone: 800-591-2284  
Fax: 740-881-2791  
Email: [sdunnpe@dandyproducts.com](mailto:sdunnpe@dandyproducts.com)  
Web: [www.dandyproducts.com](http://www.dandyproducts.com)

## 1.0 Description:

1.1 Work covered under this item consists of installing a Dandy Sack® Framed Model inlet protection system. The purpose is to keep silt, sediment, and construction debris out of the storm water system.

## 2.0 Material:

2.1 The Dandy Sack® Framed Model inlet protection unit shall be a **sewn in the U.S.A.** geotextile fabric unit.

2.2 The Dandy Sack® Framed Model shall have lifting straps to allow removal of the unit and manual inspection of the storm water system.

2.3 The Dandy Sack® Framed Model unit shall utilize an orange monofilament fabric that is manufactured in the U.S.A. with the following characteristics:

PROPERTY	TEST METHOD	UNITS	TEST RESULTS
Tensile Strength	ASTM D4632	lbs	450 x 300
Elongation	ASTM D4632	%	38% x 21%
Trapezoidal Tear	ASTM D4533	lbs	165 x 150
CBR Puncture	ASTM D6241	lbs	1000
<b>HYDRAULIC PROPERTIES:</b>			
Apparent Opening Size (AOS)	ASTM D 4751	US Std Sieve	30
Permittivity	ASTM D 4491	sec <sup>1</sup>	4.9
Water Flow Rate	ASTM 4491	gal/min/ft <sup>2</sup>	365
% Open Area (POA)	COE - 22125-86	%	29
UV Resistance (% Retained @ 2500 hrs)	ASTM D 4355	%	70
Color			Orange <sup>1</sup>

<sup>1</sup>The color orange is a trademark of Dandy Products, Inc.

The property values listed above are effective April 2022 and are subject to change without notice.

### **3.0 Installation:**

- 3.1 Remove the grate from the catch basin.
- 3.2 *For Oil and Sediment Model; to install or replace absorbent, place absorbent pillow in unit, on the bottom (below-grade side) of the unit.*
- 3.3 Stand the grate on end. Move the top lifting straps out of the way and place the grate into the Dandy Sack® Framed Model unit so that the grate is below the top straps and above the lower straps. The grate should be cradled between the upper and lower straps.
- 3.4 Holding the lifting devices, insert the grate into the inlet, being careful that the grate remains in place and being careful not to damage the Dandy Sack® Framed Model unit.

### **4.0 Maintenance:**

- 4.1 Remove all accumulated sediment and debris from vicinity of unit after each storm event.
- 4.2 After each storm event and at regular intervals, look into the Dandy Sack® Framed Model unit. If the unit is more than 1/3 full of accumulated sediment, the unit must be emptied.
- 4.3 To empty the unit, using the lifting straps lift the unit out of the inlet and remove the grate. Transport the unit to an appropriate location for removal of the contents. Holding the dumping straps on the outside at the bottom of the unit, turn the unit upside down, emptying the contents. Reinstall unit as above.
- 4.4 *For Oil and Sediment Model; remove and replace absorbent when near saturation.*
- 4.5 Dispose of unit and/or absorbent in accord with applicable Federal, state and local environmental laws and regulations.

### **5.0 Method of Measurement:**

- 5.1 The quantity to be paid is for the actual number of Dandy Sack® Framed Model inlet protection units installed

### **6.0 Basis of Payment:**

- 6.1 The unit price shall include labor, equipment, and materials necessary to complete the work and maintain the Dandy Sack® Framed Model inlet protection units.
- 6.2 Payment for the completed work will be made at the contract prices for:

<u>ITEM</u>	<u>UNIT</u>	<u>DESCRIPTION</u>
Dandy Sack® Framed	EA	Inlet Protection